



ELECTRONICS

Product Information



Product Information

SAMSUNG TFT-LCD**MODEL NO. : LTN154X5-L02-G**

LCD Product Planning Group 1, Marketing Team

Samsung Electronics Co. , LTD.



Doc.No.	LTN154X5-L02	ISSUED DATE	2006-11-27	Page	1 / 13
---------	--------------	-------------	------------	------	--------



CONTENTS

General Description	----- (3)
1. Electrical Absolute Ratings	----- (4)
2. Optical Characteristics	----- (5)
3. Electrical Characteristics	----- (6)
3.1 TFT LCD Module	
3.2 Backlight Unit	
4. Block Diagram	----- (7)
4.1 TFT LCD Module	
4.2 Backlight Unit	
5. Input Terminal Pin Assignment	----- (8)
5.1 Input Signal & Power	
5.2 Backlight Unit	
5.3 Timing Diagrams of LVDS For Transmitting	
6. Interface Timing	----- (10)
6.1 Timing Parameters	
6.2 Timing Diagrams of interface Signal	
6.3 Power ON/OFF Sequence	
7. Outline Dimension	----- (12)

Product Information

GENERAL DESCRIPTION**DESCRIPTION**

LTN154X5 is a color active matrix TFT (Thin Film Transistor) liquid crystal display (LCD) that uses amorphous silicon TFT as a switching devices. This model is composed of a TFT LCD panel, a driver circuit, and back-light system. The resolution of a 15.4 " contains 1280 x 800 pixels and can display up to 262,144colors. 6 o'clock direction is the optimum viewing angle.

FEATURES

- Ultra High Luminance with 2-CCFL
- High Color Gamut (Typical 72%)
- Wide viewing angle (H130/ V 120)
- High contrast ratio (Ultra fine & shine view)
- Ultra High Response time (Typ. 16msec)
- WXGA (1280x800 pixels) resolution
- Low power consumption
- DE (Data enable) only mode.
- 3.3V LVDS (FPD Link) Interface with 1 pixel / clock
- Enable EDID function

APPLICATIONS

- Mega-Notebook PC
- Display terminals for AV application products
- If the usage of this product is not for PC application, but for others, please contact SEC.

GENERAL INFORMATION

Item	Specification	Unit	Note
Display area	331.2(H) X 207.0(V) (15.4"diagonal)	mm	
Driver element	a-si TFT active matrix		
Display colors	262,144		
Number of pixel	1280 x RGB x 800 (16 : 10, Wide XGA)	pixel	
Pixel arrangement	RGB vertical stripe		
Pixel pitch	0.25875(H) x 0.25875(V)	mm	
Display Mode	Normally white		
Surface treatment	Haze 0, Hardness 3H		

Product Information

MECHANICAL INFORMATION

Item		Min.	Typ.	Max.	Unit	Note
Module size	Horizontal (H)	343.7	344.0	344.3	mm	
	Vertical (V)	223.7	224.0	222.3	mm	
	Depth (D)	-	10.1	10.5	mm	(1)
Weight		-	-	830	g	

Note (1) Measurement condition of outline dimension

. Equipment : Vernier Calipers

. Push Force : 500g ·f (minimum)

1. ELECTRICAL ABSOLUTE RATINGS

(1) TFT LCD MODULE

$$V_{DD} = 3.3V, V_{SS} = GND = 0V$$

Item	Symbol	Min.	Max.	Unit	Note
Power Supply Voltage	V_{DD}	$V_{DD} - 0.3$	$V_{DD} + 0.3$	V	(1)
Logic Input Voltage	V_{DD}	$V_{DD} - 0.3$	$V_{DD} + 0.3$	V	(1)

Note (1) Within T_a ($25 \pm 2^\circ\text{C}$)

(2) BACK-LIGHT UNIT

$$T_a = 25 \pm 2^\circ\text{C}$$

Item	Symbol	Min.	Max.	Unit	Note
Lamp Current	I_L	3.0	7.0	mAmps	(1)
Lamp frequency	F_L	45	80	kHz	(1)

Note 1) Permanent damage to the device may occur if maximum values are exceeded

Functional operation should be restricted to the conditions described under normal operating conditions.



Product Information

2. OPTICAL CHARACTERISTICS

The following items are measured under stable conditions. The optical characteristics should be measured in a dark room or equivalent state.

Measuring equipment : TOPCON BM-5A

* Ta = 25 ± 2 °C, VDD=3.3V, fv= 60Hz, fdCLK = **68.94**MHz, IL = 6.0 mA

Item		Symbol	Condition	Min.	Typ.	Max	Unit
Contrast Ratio (5 Points)		CR	Normal Viewing Angle $\phi = 0$ $\theta = 0$	500	700	-	-
Response Time at Ta (Rising + Falling)		T _{RT}		-	16	25	msec
Average Luminance of White (5 Points)		Y _{L,AVE}		425	490	-	cd/m ²
Color Chromaticity (CIE)	Red	R _x		0.614	0.644	0.674	-
		R _y		0.305	0.335	0.365	
	Green	G _x		0.258	0.288	0.318	
		G _y		0.568	0.598	0.628	
	Blue	B _x		0.114	0.144	0.174	
		B _y		0.043	0.073	0.103	
	White	W _x		0.283	0.313	0.343	
		W _y	0.299	0.329	0.359		
Viewing Angle	Hor.	θ_L	CR ≥ 10	60	65	-	Degrees
		θ_H		60	65	-	
	Ver.	ϕ_H		45	60	-	
		ϕ_L		45	60	-	
13 Points White Variation		δ_L		-	-	2.2	-

3. ELECTRICAL CHARACTERISTICS

Product Information

3.1 TFT LCD MODULE

Ta= 25 ± 2°C

Item		Symbol	Min.	Typ.	Max.	Unit	Note
Voltage of Power Supply		V _{DD}	3.0	3.3	3.6	V	
Differential Input Voltage for LVDS Receiver Threshold	High	V _{IH}	-	-	+100	mV	V _{CM} = +1.2V
	Low	V _{IL}	-100	-	-	mV	
Vsync Frequency		f _v	-	60	-	Hz	
Hsync Frequency		f _H	-	48.96	-	KHz	
Main Frequency		f _{DCLK}	54.3	68.94	75	MHz	
Rush Current		I _{RUSH}	-	-	1.5	A	
Current of Power Supply	White	I _{DD}	-	300	-	mA	
	Mosaic		-	310	-	mA	
	V. Stripe		-	400	480	mA	

Note (1) Display data pins and timing signal pins should be connected.(GND = 0V)

(2) f_v = 60Hz, f_{DCLK} = 68.94MHZ, V_{DD} = 3.3V , DC Current.

(3) Power dissipation pattern

3.2 BACK-LIGHT UNIT

The backlight system is an edge - lighting type with dual CCFL (Cold Cathode Fluorescent Lamp).

The characteristics of a single lamp are shown in the following tables.

INVERTER : SIC-1801


Ta= 25 ± 2 °C

Item	Symbol	Min.	Typ.	Max.	Unit	Note
Lamp Current	I _L	3.0	6.0	6.5	mArms	
Lamp Voltage	V _L	-	715	-	Vrms	I _L =6.5mA
Frequency	f _L	50	60	65	KHz	
Power Consumption	P _L		4.29		W	I _L =6.0mA
Operating Life Time	Hr	10,000			Hour	
Startup Voltage	V _s	-	-	1,250	Vrms	25°C
				1,450	Vrms	0°C
Lamp startup time		-	-	1.0	sec	


Product Information

4. BLOCK DIAGRAM

4.1 TFT LCD Module



4.2 BACK-LIGHT UNIT



Note) The output of the inverter may change according to the material of the reflector.



Product Information

5. INPUT TERMINAL PIN ASSIGNMENT

5.1. Input Signal & Power LVDS, Connector : (JAE, FI-XB30SL-HF10 or Compatible)
Mating Connector :(JAE FI-X30M or Compatible)

PIN #	SYMBOL	FUNCTION	POLARITY	REMARK
1	VSS	Ground		
2	VDD	Power Supply, 3.3 V (typical)		
3	VDD	Power Supply, 3.3 V (typical)		
4	V EEDID	DDC 3.3V power		NC if not used
5	NC	No connect		
6	Clk EEDID	DDC Clock		NC if not used
7	DATA EEDID	DDC Data		NC if not used
8	RxIN0-	LVDS differential data input	Negative	R0-R5, G0
9	RxIN0+	LVDS differential data input	Positive	
10	VSS	Ground		
11	RxIN1-	LVDS differential data input	Negative	G1-G5, B0-B1
12	RxIN1+	LVDS differential data input	Positive	
13	VSS	Ground		
14	RxIN2-	LVDS differential data input	Negative	B2-B5, HS,VS,DE
15	RxIN2+	LVDS differential data input	Positive	
16	VSS	Ground		
17	ClkIN-	LVDS differential clock input	Negative	
18	ClkIN+	LVDS differential clock input	Positive	
19	VSS	Ground		
20	NC	No connect		
21	NC	No connect		
22	NC	No connect		
23	NC	No connect		
24	NC	No connect		
25	NC	No connect		
26	NC	No connect		
27	NC	No connect		
28	NC	No connect		
29	NC	No connect		
30	NC	No connect		


Product Information

5.2 BACK LIGHT UNIT

Connector : JST BHTR - 02VS -1 * 2pcs

Pin No.	Symbol	Color	Function
1	HOT	Blue / Pink	High Voltage
2	COLD	Black/ White	Low Voltage

5.3 Timing Diagrams of LVDS For Transmission




6. INTERFACE TIMING

Product Information

6.1 Timing Parameters

Signal	Item	Symbol	Min.	Typ.	Max.	Unit	Note
Frame Frequency	Cycle	TV	804	816	1000	Lines	-
Vertical Active Display Term	Display Period	TVD	-	800	-	Lines	-
One Line Scanning Time	Cycle	TH	1350	1408	1550	Clocks	-
Horizontal Active Display Term	Display Period	THD	-	1280	-	Clocks	-


6.2 Timing diagrams of interface signal



6.3 Power ON/OFF Sequence

Product Information

: To prevent a latch-up or DC operation of the LCD module, the power on/off sequence should be as the diagram below.



Power ON/OFF Sequence

- T1 : Vdd rising time from 10% to 90%
T2 : The time from Vdd to valid data at power ON.
T3 : The time from valid data off to Vdd off at power Off.
T4 : Vdd off time for Windows restart
T5 : The time from valid data to B/L enable at power ON.
T6 : The time from valid data off to B/L disable at power Off.

NOTE.

- (1) The supply voltage of the external system for the module input should be the same as the definition of VDD.
- (2) Apply the lamp voltage within the LCD operation range. When the back-light turns on before the LCD operation or the LCD turns off before the back-light turns off, the display may momentarily become white.
- (3) In case of VDD = off level, please keep the level of input signals on the low or keep a high impedance.
- (4) T4 should be measured after the module has been fully discharged between power off and on period.
- (5) Interface signal shall not be kept at high impedance when the power is on.

Doc.No.	LTN154X5-L02	ISSUED DATE	2006-11-27	Page	11 / 13
---------	--------------	-------------	------------	------	---------



7. MECHANICAL OUTLINE DIMENSION

Product Information

[Refer to the next page]

www.panelook.com

Doc.No.	LTN154X5-L02	ISSUED DATE	2006-11-27	Page	12 / 13
---------	--------------	-------------	------------	------	---------

